



Hydraulic &
Offshore Supplies

t: +44(0)191 549 7335

e: hose@hos.co.uk

w: www.hos.co.uk

Variomat Specification



Combined tube working device for cutting ring assembly and flaring



VARIOMAT
with cutting ring assembly unit



VARIOMAT
with flaring unit

Features / Equipment

- Compact and rugged table-top unit for mobile and flexible use
- Very well suited for both, assembly of most cutting rings and flaring (37° SAE, 10°) of tubes with Ø 6 - 42 mm
- Clearly arranged schedule allows for selecting the specific hydraulic pressure (according to the tube diameter and the working method)
- Manual pressure adjustment with digital display
- Short assembling times of only few seconds
- Short set-up times when changing the tube diameter or the working method



Regardless which connection method is favourite to you:

The VARIOMAT is the professional solution for both connections.

Options

- Storage box for cutting ring assembly tooling (assembling connections and counter-support plates)

Technical data	
Tube diameter range (OD)	6 - 42 mm
Hydraulics	3.7 l/min
Capacity of the hydraulic tank	3 l
Maximum hydraulic pressure	200 bar
Feed rate of the piston	7.5 mm/s
Dimensions (WxHxD)	535 x 285 x 500 mm
Weight, approx.	65 kg
Power requirement	1.2 kW



Contact Us

Tel: +44(0)191 549 7335

Email: hos@hos.co.uk

Web: www.hos.co.uk



in

f

